

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 8297 (1976): Towing Jaw for use Between Trailers of Up to 16 Tonnes Gross Mass and Transport Tractor [TED 22: Transport Tractors and Trailers]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



Indian Standard

SPECIFICATION FOR
TOWING JAW FOR USE BETWEEN TRAILERS
OF UP TO 16 TONNES GROSS MASS AND
TRANSPORT TRACTOR

UDC 629.114.3.013 : 621.868.238.2.061.1



© Copyright 1977

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Price Rs. 5.00
Gr. 2

April 1977

Indian Standard

SPECIFICATION FOR TOWING JAW FOR USE BETWEEN TRAILERS OF UP TO 16 TONNES GROSS MASS AND TRANSPORT TRACTOR

Transport Tractors and Trailers Sectional Committee, MCPD 10

Chairman

SHRI K. RAMACHANDRAN

Representing

Ashok Leyland Ltd, Madras

Members

SHRI R. RAMAKRISHNAN (Alternate to
Shri K. Ramachandran)

SHRI V. ANAND

Research, Designs & Standards Organization
(Ministry of Railways), Lucknow

SHRI B. M. CHOPRA (Alternate)

SHRI S. B. CHANDOKKAR

Kirloskar Oil Engines Ltd, Pune

SHRI A. D. ARJUNWADKAR (Alternate)

SHRI S. P. DAYANITHY

Ministry of Defence (DGI)

MAJ D. V. KHER (Alternate)

BRIG G. K. GOKHALE

Bharat Earth Movers Ltd, Bangalore

SHRI K. T. SAMPATHGOPAL (Alternate)

SHRI B. D. KERAWALLA

The Premier Automobiles Ltd, Bombay

SHRI G. Y. BHATT (Alternate)

SHRI N. H. KESWANI

Ministry of Shipping & Transport (Roads Wing)

SHRI K. R. NATARAJ

Southern Roadways Pvt Ltd, Madurai

SHRI B. R. PAHOJA

Khushiram Tarachand Pvt Ltd, Bombay

SHRI G. R. REDDY

The Hyderabad Allwyn Metal Works Ltd,
Hyderabad

SHRI I. K. SAMA

Indian Tyre Technical Advisory Committee,
Sahaganj

SHRI K. P. MITRA (Alternate)

SHRI B. K. SATAPATHY

Hindustan Motors Ltd, Hooghly

SHRI R. C. SETHI

Vehicle Research & Development Establishment
(Ministry of Defence), Ahmednagar

SHRI A. M. SHAH

Mahindra Owen Ltd, Pune

SHRI P. D. DESHPANDE (Alternate)

(Continued on page 2)

© Copyright 1977

INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS : 8297 - 1976

(Continued from page 1)

Members

SHRI K. SRINIVASAN

SHRI R. G. LYNN (*Alternate*)

SHRI P. S. DAS,
Director (MCPD)

Representing

Tata Engineering & Locomotive Co Ltd,
Jamshedpur

Director General, ISI (*Ex-officio Member*)

Secretary

SHRI S. CAPOOR
Deputy Director (MCPD), ISI

Indian Standard

SPECIFICATION FOR TOWING JAW FOR USE BETWEEN TRAILERS OF UP TO 16 TONNES GROSS MASS AND TRANSPORT TRACTOR

0. FOREWORD

0.1 This Indian Standard was adopted by the Indian Standards Institution on 31 December 1976, after the draft finalized by the Transport Tractors and Trailers Sectional Committee had been approved by the Marine, Cargo Movement and Packaging Division Council.

0.2 The requirements of this standard, which relate only to vehicles used on the public highways, are intended to ensure the maximum degree of compatibility between commercial and government department standards.

0.3 Towing jaws may be forged or cast.

0.4 The material specifications are for the minimum qualities acceptable, and do not exclude the use of other materials provided that these are at least equal in quality so that road safety is not impaired.

0.5 This standard should be used in conjunction with IS : 8274-1976*. The jaw has been designed to accommodate a drawbar eye of 51 mm internal diameter and 40 mm stock or 76 mm internal diameter and 40 mm stock.

0.6 The standard applies to connections to trailers of up to 16 tonnes gross mass. The specification for a towing jaws for connections to trailer of up to 35 tonnes gross mass is given in IS : 8296-1976† and for trailers of up to 5 tonnes gross mass is given in IS : 8298-1976‡.

0.7 In the preparation of this standard, considerable assistance has been derived from BS AU 26 : 1964 'Specification for towing jaw for use between trailers of 5-16 tonnes gross weight and towing vehicle', issued by the British Standards Institution.

*Specification for draw bar eyes and forecarriage pins for connection between trailers of gross mass above 5 and up to 35 tonnes and transport tractor.

†Specification for towing jaw for use between trailers of up to 35 tonnes gross mass and transport tractor.

‡Specification for towing jaw for use between trailers of up to 5 tonnes gross mass and transport tractor.

1. SCOPE

1.1 This standard specifies the basic dimensions and quality of materials for a towing jaw and its mountings, for use in connection between a transport tractor and a trailer of up to 16 tonnes gross mass.

1.2 The gross mass refers to gross laden train masses where more than one trailer is drawn.

2. MATERIALS

2.1 The jaw shall be made from a material of quality not less than Grade C20 of IS : 1875-1971* for steel in normalized condition for the forged jaw and Grade 23-45 of IS : 1030-1974† for the cast jaw.

2.2 The towing pin shall be made from a material of quality not less than Grade 35Mn2Mo 28 steel of IS : 5517-1969‡.

3. DIMENSIONS

3.1 Dimensions shall be as shown in Fig. 1. The dimensions marked with asterisk (*) are essential for interchangeability, other dimensions apply to the forged jaw and are for guidance only.

NOTE — The dimensions specified for the forged jaws have been calculated on the basis of the total yield strength being not less than two-thirds the gross mass being towed. It is necessary that any other part not covered by this standard, connecting the coupling to the towing tractor shall have a similar strength.

4. DESIGN

4.1 An efficient safety locking device shall be provided as indicated in Fig. 1 to prevent accidental extraction of the towing pin from the jaw.

4.2 The jaw shall be so designed that a bar of 44 mm diameter shall pass freely between the pin and the inside face of the jaw (see Fig. 1).

5. MOUNTING

5.1 The jaw shall be mounted with four bolts of 16 mm diameter conforming to designation M 16 × 1.5 (P) of IS : 1364-1967§ at 100.0 × 100.0 mm centres. This renders it interchangeable in mounting with hooks specified in IS : 8299-1976|| and IS : 8300-1976¶.

*Specification for carbon steel billets, blooms, slabs and bars for forgings (third revision).





†Specification for carbon steel castings for general engineering purposes (second revision).

‡Specification for steel for hardening and tempering.


§Precision and semi-precision hexagon bolts, screws, nuts and lock nuts (dia range 6 to 39 mm) (first revision).

||Specification for towing hook for use between trailers of up to 16 tonnes gross mass and transport tractor.


¶Specification for towing hook for use between trailers of up to 35 tonnes gross mass and transport tractor.



SECTION BB



SECTION AA



* ESSENTIAL DIMENSIONS

SECTION CC

All dimensions in millimetres.

FIG. 1 TOWING JAW FOR TRAILERS UP TO 16 TONNES

As in the Original Standard, this Page is Intentionally Left Blank

5.2 The nuts shall be secured either by peening the end of the bolt or by fitting a positive locking device such as a safe locking nut or a slotted nut and split pin.

6. MARKING

6.1 The following wording, in clear lettering 10 mm high, raised or stamped, shall be marked on each towing jaw:

- a) ' TO TOW 16 TONNES GROSS ' on one side, and
- b) ' IS : 8297-1976 ' on the other side.

6.2 In addition, the towing jaws shall also be marked at the appropriate place, the following information:

- a) Name or trade-mark of the manufacturer,
- b) Date or year of manufacture, and
- c) The country of manufacture.

6.2.1 The towing jaw may also be marked with the ISI Certification Mark.

NOTE — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

INDIAN STANDARDS
ON
TRANSPORT TRACTORS AND TRAILERS

IS:

- 6763 (Part I)-1972 Specification for fifth wheel king pins for trailers: Part I 50·8 mm diameter
- 6763 (Part II)-1976 Specification for fifth wheel king pins for trailers: Part II 89 mm diameter
- 7774 (Part I)-1975 Glossary of terms relating to transport tractors and trailers: Part I Basic terms
- 7774 (Part II)-1975 Glossary of terms relating to transport tractors and trailers: Part II Dimensions and weights
- 8007-1976 Dimension of fifth wheel coupling between transport tractors and semi/articulated trailers for interchangeability
- 8037-1976 General requirements for transport tractor-trailers
- 8274-1976 Specification for drawbar eyes and forecarriage pins for connection between trailers of gross mass above 5 and up to 35 tonnes and transport tractor
- 8296-1976 Specification for towing jaw for use between trailers of up to 35 tonnes gross mass and transport tractor
- 8297-1976 Specification for towing jaw for use between trailers of up to 16 tonnes gross mass and transport tractor
- 8298-1976 Specification for towing jaw for use between trailers of up to 5 tonnes gross mass and transport tractor
- 8299-1976 Specification for towing hook for use between trailers of up to 16 tonnes gross mass and transport tractor
- 8300-1976 Specification for towing hook for use between trailers of up to 35 tonnes gross mass and transport tractor

PUBLICATIONS OF INDIAN STANDARDS INSTITUTION

INDIAN STANDARDS

Over 9 000 Indian Standards covering various subjects have been issued so far. Of these, the standards belonging to the Marine, Cargo Movement and Packaging Group fall under the following categories:

MARINE

Anchors and anchor cables
Diesel engines
Distress signals
Fire safety
Inland vessels
Life saving equipment & accessories
Magnetic compasses
Mooring equipment
Navigational lights
Piping systems, valves & accessories
Ship's derricks and accessories
Ship's side scuttles & windows
Ventilation
Miscellaneous

CARGO MOVEMENT

Cargo marking, handling and stowing

Freight containers

Industrial trucks, tractors and trailers

Lifting chains, associated fittings and components

Non-powered materials handling equipment

Pallets

Transport tractors and trailers

PACKAGING

Glass containers

Metal containers

Paper and flexible packaging

Plastics containers

Wood and wood products containers

OTHER PUBLICATIONS

ISI Bulletin (Published every month)

Single Copy	Rs 4-00
-------------	-----	-----	-----	-----	-----	---------

Annual Subscription	Rs 36-00
---------------------	-----	-----	-----	-----	-----	----------

Standards : Monthly Additions

Single Copy	Rs 0-30
-------------	-----	-----	-----	-----	-----	---------

Annual Subscription	Rs 3-00
---------------------	-----	-----	-----	-----	-----	---------

Annual Reports (from 1948-49 onwards)	Rs 2-00 to 6-00
---	-----	-----	-----	-----	-----	-----------------

ISI Handbook, 1975	Rs 30-00
--------------------	-----	-----	-----	-----	-----	----------

INDIAN STANDARDS INSTITUTION

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephone : 27 01 31 (20 lines)

Telegrams : Manaksanstha

Regional Offices:

Western : Novelty Chambers, Grant Road

Eastern : 5 Chowringhee Approach

Southern : C. I. T. Campus, Adyar

BOMBAY 400007	37 97 29
---------------	----------

CALCUTTA 700072	23-08 02
-----------------	----------

MADRAS 600020	41 24 42
---------------	----------

Branch Offices:

Pushpak, Nurmohamed Sheikh Marg, Khanpur

'F' Block, Unity Bldg, Narsimharaja Square

Ahimsa Bldg, SCO 82-83, Sector 17C

5-8-56/57 L. N. Gupta Marg

117/418 B Sarvodaya Nagar

B. C. I. Bldg (3rd Floor), Gandhi Maidan East

Hantex Bldg (2nd Floor), Rly Station Road

AHMADABAD 380001	2 03 91
------------------	---------

BANGALORE 560002	2 76 49
------------------	---------

CHANDIGARH 160017	2 83 20
-------------------	---------

HYDERABAD 500001	4 57 11
------------------	---------

KANPUR 208005	32 72
---------------	-------

PATNA 800004	5 36 55
--------------	---------

TRIVANDRUM 695001	32 27
-------------------	-------